

Precision Test Adapters

1.35 mm(F) to 1.85 mm(M)

withwave

Versatile RF & MW Test Solutions

Withwave's Precision Test Adapters are designed based on precision microwave interconnection technologies. **This 1.35 mm(F) to 1.85 mm(M)** adapter is manufactured to precise microwave specifications and constructed with female gender on 1.35mm side and male gender on 1.85mm side. The precision microwave connector interfaces ensure an excellent microwave performance up to 67 GHz



■ Features

- Frequency range : DC to 67 GHz
- VSWR : 1.3 : 1(Max) @ 67 GHz
- Stainless steel (passivated)

■ Specification

Scope	Specification	AD01F26MS1
Electrical	Impedance(Ohm)	50
	Operation Freq.(GHz)	DC to 67 GHz
	VSWR (Max)	1.3 : 1 @ 67 GHz
Material	Dielectric	Ultem 1000
	Center Contact	Beryllium copper with gold plated
	Body	Passivated Stainless Steel

* RoHS Compliant

Precision Test Adapters

1.35 mm(F) to 1.85 mm(M)


withwave

Versatile RF & MW Test Solutions

■ Drawing

Part No.: AD01F26MS1

Unit : mm



■ Test Result

▪ Frequency : 10 MHz to 67 GHz

