


A B C D E F

<Specification>

- 1. Material
 - 1) Body : Stainless Steel (Passivated)
Beryllium Copper (Au Plated)
 - 2) Center Conductor : Beryllium Copper(Au Plated)
 - 3) Insulator : PTFE / ULTEM
- 2. Electrical
 - 1) Impedance : 50Ω
 - 2) Frequency range : DC to 40GHz
 - 3) VSWR(dB) : 1.22 : 1(-20dB)
 - 4) Withstanding Voltage : 500Vrms min
- 3. Mechanical
 - 1) Durability : 100 Cycles (FD)
- 4. Environmental
 - 1) Temp. Range : -40℃ to +125℃
 - 2) RoHS Compliant



THE INFORMATION HEREON/HEREIN IS PROPRIETARY TO WITH-WAVE CO., LTD. IT SHALL NOT BE COUPIED, DISCLOSED OR USED(PARTIALLY OR WHOLLY) IN ANY MANNER WITHOUT PRIOR EXPRESSED WRITTEN AUTHORIZATION OF WITH-WAVE CO., LTD.

Tolerance	Dimension	Range	Angle	Date	2022. 10. 17	Title	SMP(M) to 2.92mm(M) Adapter
	0	±0.1	±2.0°	Approved	..	Part No.	AD05M03MS1
	0.X	±0.05	±1.0°	Checked	.		
0.XX	±0.03			Drawn	SUN.		
Scale		Unit	mm				

A B C D E F