

A

B

C

D

E

F

<Specification>

1. Material

- 1) Body : Brass (Ternary alloy)
- 2) Center Conductor : BeCu (Silver Plated)
- 3) Insulator : PTFE

2. Electrical

- 1) Impedance : 50Ω
- 2) Frequency range : DC to 6GHz
- 3) VSWR(dB) : 1.25 : 1(-19dB)
- 4) Passive Intermodulation : -160 dBc
(IM3 using 2x43dBm)


3. Mechanical

- 1) Durability : 500 Cycles

4. Environmental

- 1) Temp. Range : -40°C to +125°C
- 2) RoHS Compliant

2-DIN (Female)



THE INFORMATION HEREON/HEREIN IS PROPRIETARY TO WITH-WAVE CO., LTD. IT SHALL NOT BE COUPIED, DISCLOSED OR USED(PARTIALLY OR WHOLLY) IN ANY MANNER WITHOUT PRIOR EXPRESSED WRITTEN AUTHORIZATION OF WITH-WAVE CO., LTD.

Tolerance	Dimension	Range	Angle	Date	2021. 05. 13	Title	DIN(F) to DIN(F) Adapter	
	0	±0.1	±2.0 °	Approved	..	Part No.	AD21F21FS1	
	0.X	±0.05	±1.0 °	Checked	.			
	0.XX	±0.03		Drawn	Teri K			
Scale		Unit	mm			withwave		Rev. —