




<Specification>

1. Material

- 1) Body : Brass (Ternary alloy)
- 2) Center Conductor : BeCu (Silver Plated)
- 3) Insulator : PTFE
- 4) C-ring : Stainless Steel (Passivated)
- 5) Coupling Nut : Brass (Ternary alloy)

2. Electrical

- 1) Impedance : 50Ω
- 2) Frequency range : DC to 6GHz
- 3) VSWR(dB) : 1.22 : 1(-20dB)
- 4) Withstanding Voltage : 2,500Vrms min
- 5) Insulation Resistance : 5,000M Ω Min
- 6) Passive Intermodulation : -160 dBc (IM3 using 2x43dBm)

3. Mechanical

- 1) Durability : 500 Cycles

4. Environmental

- 1) Temp. Range : -40°C to +125°C
- 2) RoHS Compliant

THE INFORMATION HEREON/HEREIN IS PROPRIETARY TO WITH-WAVE CO., LTD. IT SHALL NOT BE COUPIED, DISCLOSED OR USED(PARTIALLY OR WHOLLY) IN ANY MANNER WITHOUT PRIOR EXPRESSED WRITTEN AUTHORIZATION OF WITH-WAVE CO., LTD.

Tolerance	Dimension	Range	Angle	Date	2021. 05. 13	Title	DIN(M) to N(F) Adapter	
	0	±0.1	±2.0 °	Approved	..	Part No.	AD21M07FS1	
	0.X	±0.05	±1.0 °	Checked	.			
	0.XX	±0.03		Drawn	Ter i K			
Scale		Unit	mm			withwave		Rev. —