

A

B

C

D

E

F

<Specification>


1

1. Material

- 1) Connector : 0.8mm Female(STS303, Passivated)
- 2) Cable : W602 Cable
- 3) Adhesive Shrink Tube(Black)
- 4) Marking tube(white)

2

XX + "A"



3

2. Electrical

- 1) Impedance : 50Ω
- 2) Frequency range : DC to 145GHz
- 3) VSWR : 1.65 : 1(DC to 145GHz)
Assembly to be 100% tested for Return loss and Insertion loss.
- 4) Velocity of propagation : 70%

3. Mechanical

- 1) Mating cycles : 500

4. Environmental

- 1) Temp. Range : -40°C to +85°C
- 2) RoHS Compliant

- 5) Cable Assembly to have protective cap assembled on each end and to be individually packaged in bag with test report.

4

Model (Part No.)	XX (Length)	"A" (Tolerance)
W602-DF1DF1-6 inch	6 inch (152.4mm)	+0.157 inch / -0 (+4.0mm / -0.0)
W602-DF1DF1-12 inch	12 inch (304.8mm)	+0.196 inch / -0 (+5.0mm / -0.0)
W602-DF1DF1-24 inch	24 inch (609.6mm)	+0.393 inch / -0 (+10.0mm / -0.0)

THE INFORMATION HEREON/HEREIN IS PROPRIETARY TO WITH-WAVE CO., LTD. IT SHALL NOT BE COPIED, DISCLOSED OR USED(PARTIALLY OR WHOLLY) IN ANY MANNER WITHOUT PRIOR EXPRESSED WRITTEN AUTHORIZATION OF WITH-WAVE CO., LTD.

Scale	N/A	Date	2025.12.01
Unit	inch	Drawn	Teri K

Title	W602 Cable Assembly 0.8mm(F)-0.8mm(F) Connector
Part No.	W602-DF1DF1-xx

withwave

4

A

B

C

D

E

F