

A

B

C

D

E

F


## &lt;Specification&gt;

1

## 1. Material

- 1) Connector1 : 2.92mm Male(STS303, Passivated)
- 2) Connector2 : SMA Male(STS303, Passivated)
- 3) Cable : WT100 Cable
- 4) Adhesive Shrink Tube(Black)
- 5) Marking tube(white)

2



3

## 2. Electrical

- 1) Impedance :  $50\Omega$
- 2) Frequency range : DC to 26.5GHz
- 3) VSWR : 1.3 : 1(DC to 26.5GHz)  
Assembly to be 100% tested for Return loss and Insertion loss.
- 4) Withstanding Voltage : 500Vrms max.  
Assembly to be 100% tested for Opens, Shorts & Hipot tested(AC or DC).  
The Hipot voltage for the assembly should be set to the end option with the lowest test voltage rating.
- 5) Velocity of propagation : 76%

4

## 3. Mechanical

- 1) Durability : 500 Cycles

## 4. Environmental

- 1) Temp. Range :  $-40^{\circ}\text{C}$  to  $+85^{\circ}\text{C}$
- 2) RoHS Compliant

- 5) Cable Assembly to have protective cap assembled on each end and to be individually packaged in bag with test report.

Model (Part No.)	XX (Length)	"A" (Tolerance)
WT100-KM1SM1-6 inch	6 inch (152.4mm)	+0.157 inch / -0    (+4.0mm / -0.0)
WT100-KM1SM1-12 inch	12 inch (304.8mm)	+0.196 inch / -0    (+5.0mm / -0.0)
WT100-KM1SM1-24 inch	24 inch (609.6mm)	+0.393 inch / -0    (+10.0mm / -0.0)

THE INFORMATION HEREON/HEREIN IS PROPRIETARY TO WITH-WAVE CO., LTD. IT SHALL NOT BE COPIED, DISCLOSED OR USED(PARTIALLY OR WHOLLY) IN ANY MANNER WITHOUT PRIOR EXPRESSED WRITTEN AUTHORIZATION OF WITH-WAVE CO., LTD.

Scale      N/A      Date      2025. 12. 01  
Unit      inch      Drawn      MS. Kim

Title	WT100 Cable Cable Assembly 2.92mm(M)-SMA(M) Connector		
Part No.	WT100-KM1SM1-XX		
withwave		Rev.	-

A

B

C

D

E

F