



1. Material
  - 1) Connector : 2.92mm Male(STS303, Passivated)
  - 2) Cable : WT400 Cable
  - 3) Adhesive Shrink Tube(Black)
  - 4) Marking tube(white)
2. Electrical
  - 1) Impedance : 50Ω
  - 2) Frequency range : DC to 40GHz
  - 3) VSWR : 1.3 : 1(DC to 40GHz)  
Assembly to be 100% tested for Return loss and Insertion loss.
  - 4) Withstanding Voltage : 800Vrms max.  
Assembly to be 100% tested for Opens, Shorts & Hipot tested(AC or DC).  
The Hipot voltage for the assembly should be set to the end option with the lowest test voltage rating.
  - 5) Velocity of propagation : 83%
3. Mechanical
  - 1) Durability : 500 Cycles
4. Environmental
  - 1) Temp. Range : -40℃ to +85℃
  - 2) RoHS Compliant
5. Cable Assembly to have protective cap assembled on each end and to be individually packaged in bag with test report.



Model (Part No.)	XX (Length)	"A" (Tolerance)
WT400-KM1KM1-6 inch	6 inch (152.4mm)	+0.157 inch / -0 ( +4.0mm / -0.0)
WT400-KM1KM1-12 inch	12 inch (304.8mm)	+0.196 inch / -0 ( +5.0mm / -0.0)
WT400-KM1KM1-24 inch	24 inch (609.6mm)	+0.393 inch / -0 ( +10.0mm / -0.0)

THE INFORMATION HEREON/HEREIN IS PROPRIETARY TO WITH-WAVE CO., LTD. IT SHALL NOT BE COPIED, DISCLOSED OR USED(PARTIALLY OR WHOLLY) IN ANY MANNER WITHOUT PRIOR EXPRESSED WRITTEN AUTHORIZATION OF WITH-WAVE CO., LTD.

Scale	N/A	Date	2025. 12. 01
Unit	inch	Drawn	MS. Kim

Title	WT400 Cable Assembly 2.92mm(M)-2.92mm(M) Connector	
Part No.	WT400-KM1KM1-xx	
1		Rev.
		—